

Z MASTER[®]

5000 SERIES

PRODUCTIVE FROM TOP TO BOTTOM.



When you cover a lot of ground, you need a machine that keeps up. Toro's Z Master[®] 5000 Series packs the power, fuel efficiency and comfort you demand.

4.4–6.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.



COMFORTABLE RIDE

The deluxe suspension seat features thick cushions, large bolsters and 3-D isolator mounts that absorb bumps and vibrations to reduce operator fatigue.



SMART HOUR METER

Maintain your mower at the proper service intervals. Service reminders, PTO and maintenance (hydro/oil) hours, and battery voltage are easy to read on the large display screen.



EFI FUEL EFFICIENCY

The environmentally friendly design exceeds requirements for CARB Tier III and EPA Phase III, and keeps emissions as low as possible by continuing to run at optimal levels.



HIGH-STRENGTH BLADES

Pick your performance. Match the blade to the job for an outstanding cut everytime.

	MyRIDE [®] SUSPENSION SYSTEM				MyRIDE [®] SUSPENSION SYSTEM											
	72906 [†]	72955	72910	72930	72911	72951	72918	72912								
POWER SYSTEM																
Commercial Engines at 3600 RPM*	25 hp Kohler [®] Command PRO EFI (747cc)		25.5 hp Kawasaki [®] FX801		25 hp Kohler Command PRO EFI (747cc)		▶ 26.5 hp Kohler Command PRO EFI (747cc)									
Starter	Electric															
Heavy-Duty Canister Air Cleaner	Standard															
Drive Tires	23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		▶ 24" x 12" – 12" Tweels • (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)									
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)															
Fuel/Capacity	Gas/12-Gal (45.4 L)															
Hour Meter	Smart Hour Meter		Standard		Smart Hour Meter											
Hydraulic Drive System	Unitized Pump & Wheel Motors															
Pump	12cc/re (shock valves)															
Wheel Motor	14.6 cir															
Maximum Forward Speed	10 mph (16.1 km/h)															
Clutch	Electromagnetic															
MOWING DECKS																
Deck Size	52" (132.1 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	72" (182.9 cm)								
Cutting Deck	7-Gauge TURBO FORCE															
Bullnose Bumper	Standard															
Adjustable Discharge Baffle	Standard, tools-free															
Rubber Discharge Chute	Standard															
Deck Lift Design	Extension Spring															
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum															
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard															
Spindle Bearings	Maintenance-Free															
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)															
Blades	.204" (.5 cm) Heat-Treated Steel															
Blade Tip Speed	18,500+ ft/min															
Belt Construction	Aramid Fiber V-Belt															
Anti-Scalp Rollers	3 Standard, 1 Optional		4 Standard, 1 Optional				▶ 6 Standard, 1 Optional									
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)															
FEATURES																
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened															
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts	▶ MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts		▶ MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts								
Armrests	Standard															
Seat Suspension System	Standard															
Folding ROPS	Standard															
Storage Compartment	Standard															
Foot Pedal Deck Lift	Standard															
Z Stand	Optional															
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access															
WEIGHTS AND MEASUREMENTS																
Weight	1,168 lbs.	529.8 kg	1,259 lbs.	571 kg	1,216 lbs.	551.6 kg	1,255 lbs.	569.3 cm	1,255 lbs.	569.3 cm	1,304 lbs.	591.5 cm	1,296 lbs.	587.9 kg	1,296 lbs.	587.9 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	53.7"	136.4 cm	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm
Deflector Width	67.6"	171.7 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm
Length	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.
[†]CARB compliant model or model available.

▶ = Step Up Feature