

## GP2500A NEW

### Portable Generators



**WACKER  
NEUSON**  
*all it takes!*



### Dependable portable power

This lightweight, versatile generator is ideal for smaller jobs. It's durable and compact size offers dependable high performance power with unmatched tool starting ability and voltage regulation. Premium components provide long, trouble-free operation.

- A unique step-start generator technology with Automatic Voltage Regulation (AVR) and separate excitation winding delivers best in class tool starting and voltage regulation.
- Robust, powder coated steel frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock mounting combine to provide outstanding impact protection.
- Proven Honda GX160 engine with low-oil shut down.
- Fully compliant with EPA evaporative emissions regulations

## GP2500A NEW Technical specifications

### Portable Premium Generators

#### Dimensions

|                      |                       |
|----------------------|-----------------------|
| L x W x H            | 24.5 x 17.2 x 19.3 in |
| L x W x H - Shipping | 25.2 x 18.0 x 20.6 in |
| Shipping weight      | 104 lb                |

#### Operating data

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Operating weight                    | 218 lb                          |
| Continuous output                   | 2,250 kVA                       |
| Circuit breaker AC - 1 Phase 1 Pole | 20 A                            |
| Receptacles                         | (1) 125V, 20A GFCI Duplex 5-20R |

#### Electrical system

|                              |                  |
|------------------------------|------------------|
| Voltage AC - 1 Phase         | 120 V            |
| Frequency                    | 60 Hz            |
| Power factor                 | 1 cos $\Phi$ 1~  |
| Generator model              | AVR with Brushes |
| Generator insulation (class) | B                |
| Power Rating Specification   | SAE J1349        |

#### Engine / Motor

|                       |                     |
|-----------------------|---------------------|
| Engine / Motor        | Honda GX160         |
| Cylinder              | 1                   |
| Displacement          | 9.9 in <sup>3</sup> |
| Operating performance | 4.8 kW              |
| RPM / speed           | 3,600 rpm           |
| Tank capacity Oil     | 0.7 US qt           |
| Tank capacity Fuel    | 3.17 US gal         |
| Fuel type             | Gasoline            |
| Fuel consumption      | 0.43 US gal/h       |
| Runtime               | 7.4 h               |

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2019 Wacker Neuson SE.