

GP3800A NEW

Portable Generators



**WACKER
NEUSON**
all it takes!



Versatile and dependable portable power

Portable generator power designed for construction and rental applications or anywhere high performance, reliable power is needed. Built with heavy-duty frames and premium components to provide long, trouble-free operation even in abusive environments. Compact and quiet generator is ideal for powering a variety of equipment including high starting amperage tools.

- Best in class tool starting and voltage regulation due to a unique step-start generator technology with Automatic Voltage Regulation (AVR) and separate excitation winding.
- Central GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures while offering personal protection on all receptacles including 240 Volt. Meets the latest NEC and OSHA jobsite standards.
- Unique auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear.
- Robust, powder coated steel frame with dual cross-member support, high impact polyethylene fuel tank and

heavy duty shock-mounting combine to provide outstanding impact protection.

- Proven Honda GX240 engine with low-oil shutdown. Fully compliant with the latest EPA evaporative emissions regulations.

GP3800A NEW Technical specifications

Portable Premium Generators

Dimensions

L x W x H	28.0 x 21.6 x 20.3 in
L x W x H - Shipping	28.6 x 22.4 x 21.6 in
Shipping weight	157 lb

Operating data

Operating weight	196 lb
Continuous output	3,400 kVA
Circuit breaker AC - 1 Phase 2 Pole	16 A
Receptacles	(2) 125V, 20A duplex 25-20R
Receptacles	(1) 125/250V, 20A twist lock L14-20R
Receptacles	(1) 125V, 30A twist lock L5-30R

Electrical system

Voltage AC - 1 Phase	120/240 V
Frequency	60 Hz
Power factor	1 cos Φ 1~
Generator model	AVR with Brushes
Generator insulation (class)	B
Power Rating Specification	SAE J1349

Engine / Motor

Engine / Motor	Honda GX240
Cylinder	1
Displacement	16.5 in ³
Operating performance	7.9 kW
RPM / speed	3,600 rpm
Tank capacity Oil	1.2 US qt
Tank capacity Fuel	5.5 US gal
Fuel type	Gasoline
Fuel consumption	0.6 US gal/h
Runtime	8.8 h

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2019 Wacker Neuson SE.